



410 TX™ Bass Enclosure

SPECIFICATIONS

SPECIFICATIONS

Frequency Response:

1 meter on-axis swept sine in anechoic environment:

30 Hz - 15 kHz

Power Handling:

350 W RMS continuous

700 W program

Transducer Complement:

Four 10" *Kevlar® impregnated woofers

One Phenolic dome horn tweeter

Box Tuning Frequency:

40 Hz

Crossover Frequency:

3.5 kHz

Impedance, Z:

8 ohms (nominal)

6.9 ohms (minimum)

Input Connections:

One 1/4" phone jack

Enclosure Materials and Finish:

3/4" plywood, carpet covered with metal corners and an expanded metal grille

Dimensions (H x W x D):

25.250" x 24.500" x 17.250"

(64.1 cm x 62.2 cm x 43.8 cm)

DESCRIPTION

The 410 TX™ is one of the hottest bass enclosures from Peavey. The 10" drivers were developed specifically for the 410 TX. To decrease unwanted distortion, *Kevlar® impregnated cones were used in these drivers. Increased low frequency output is accomplished by using an enlarged vent area. The upper harmonics needed to accurately reproduce sharp, tight transients are handled by the horn loaded tweeter. An L-pad attenuator has been designed into the crossover so that the amount of these high frequencies can be custom tailored for any style of playing or particular sound.

The 410 TX is an 8 ohm enclosure capable of handling 700 watts of peak program material. This enclosure can be used as a stand-alone device or in cabinet such as the 115 BX™.

*Kevlar® is a registered trademark of DuPont.

**ONE YEAR LIMITED
WARRANTY —**

NOTE: For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P. O. Box 2898, Meridian, Mississippi 39302-2898.



Features and specifications subject to change without notice.

©1997 **Peavey Electronics Corporation** 711 A Street / Meridian, MS 39301 / U.S.A. / (601) 483-5365 / Fax 486-1278
#80301559

Printed in U.S.A. 3/97